



Material Safety Data Sheet

Date Issued/Revised: May 9, 2008
Supersedes: N/A

Section 1: Product and Company Identification

COMPANY: Two2cool Lubricants Telephone: 863-357-3400
5868 NW 30th ST
Okeechobee, Florida 34972

#10080.....CUSTOMER PRODUCT CODE
Coolant Additive.....Two2wet Coolant Additive

www.two2cool.com/v/vspfiles/downloadables/

Section II: Components and Hazard

Information:

Hazardous Materials Identification System (HIMS)
Health 2
Flammability 1
Reactivity 0
Protective Equip B

HAZARDOUS COMPONENTS:

Lead naphthenate, PEL/ TWA, 0.05 mg/m³

Section III: Primary Routes of Entry and Emergency and First Aid Procedures:

Eye Contact: May cause eye irritation. Flush with large amounts of water, lifting upper and lower lids occasionally. Get medical attention.
Skin: May cause skin irritation. Thoroughly wash exposed area with soap and water. Remove contaminated clothing. Launder contaminated clothing before reuse.
Inhalation: May be harmful if inhaled. May cause respiratory irritation. If affected, remove individual to fresh air. If breathing is difficult, administer oxygen. If breathing is stopped, give artificial respiration. Keep person warm and quiet. Get medical attention.
Ingestion: May be harmful if swallowed. Do NOT induce vomiting. Keep person warm, quiet and get medical attention.
Aspiration of material into the lungs due to vomiting can cause chemical pneumonitis, which can be fatal.

Section IV: Fire and Explosion Hazard

Information:

Flash Point: Above 140 deg. F
Handling Precautions: Use product with caution around heat, sparks, pilot lights, static and open flame.
Extinguishing Media and Fire Fighting Procedures: Foam, water spray (fog) dry chemical, carbon dioxide and vaporizing liquid type extinguishing agents may all be suitable for extinguishing fires involving this type product. Depending on size or potential size of fire.

Section V: Health and Hazard Information

Effects of overexposure: (Signs and Symptoms):

May cause eye, skin or respiratory irritation. May be harmful if inhaled or swallowed. May cause central nervous system depression. May cause headache, and dizziness. Lead is a potent, systemic poison that serves no known useful function once absorbed into your body. Chronic overexposure to lead may result in severe damage to you blood forming, nervous, urinary, central nervous system, and reproductive organs. See OSHA Lead

Standard, CFR 1910.1025

Carcinogenicity:

NTP: Yes

IARC: Yes

OSHA: Yes

Section VI: Physical Data

Boiling Temperature: ND
Vapor Density (Air = 1) Heavier than air



Material Safety Data Sheet

Date Issued/Revised: May 9, 2008
Supersedes: N/A

Evaporation Rate: Slower than ether
Vapor Pressure: ND
Weight per Gallon: 8.3# per gallon

Section VII: Reactivity

This product is stable and will not react violently with water. Hazardous polymerization will not occur. Avoid contact with strong oxidizing agents (e.g., nitric acid, permanganates).

Section VIII: Environmental Information

Dike area of spill to prevent spreading, pump liquid into salvage tank. Remaining liquid may be taken up on sand, clay, earth, or floor absorbent. Prevent run off to sewers, streams or other bodies of water. Dispose of according to local, state and federal laws.

Section IX: Protection and Precautions

Ventilation: Provide sufficient mechanical and local exhaust ventilation

Respiratory Protection: A NIOSH/MSHA jointly approved self-contained breathing apparatus with full face piece operated in pressure demand or other positive mode is advised.

Protective Gloves: Wear resistant gloves such as Neoprene.

Eye Protection: Chemical splash goggles in compliance with OSHA regulations are advised.

Other Protective Equipment: Use chemical resistant apron or other impervious clothing, if needed, to avoid contaminating regular clothing which could result in prolonged or repeated skin contact.

Work Practices and Engineering Controls: Keep containers and storage containers closed when not in use. Do not store near heat, sparks, or open flames.

Personal Hygiene: Minimize breathing vapor, mist or fumes. Avoid prolonged or repeated contact with skin. Remove contaminated clothing; launder or dry clean before reuse. Remove contaminated shoes and clean before reuse. Wash thoroughly after contact, before breaks, meals, and at end of day.

Section X: Transportation Information

For information relative to spills resulting from transportation incidents, refer to DOT Emergency Response Guide, DOT P 5800.5. guide #26.

Section XI: Special Comments

Information and recommendations contained herein are believed to be accurate and reliable by manufacturer. Manufacturer does not warrant or guarantee accuracy and assumes no liability for damages.